
LEE BROOM

ORION GLOBE LIGHT (220-240V)





LED Driver Dimensions

10cm x 6cm x 3cm

Suitable sized cavity $\!\!\!/$ housing required for LED driver in ceiling or surface mounting.

Alternatively use deep canopy to mount LED driver in canopy.

PRODUCT DETAILS

Name

Orion Globe Light

Finish & Product Code

Polished Gold ORI0010
Polished Gunmetal ORI0011

Materials

Opal glass globe, steel tube

Illumination

7.6W, 2700k, 377 lumen, 24VDC, CRI 85 Supplied with separate LED driver with 220-240V input.

Dimming

Dimmable. Recommended dimmer for up to 8 units: Varilight V-Pro JPQ401 (120w)

For more than 8 units, please contact us.

Certification

CE, CB

 ϵ

Year of Design 2018

Dimensions

H 13cm x W 87.5cm

Suspension

Length: 500cm

I \times Adjustable steel tensile wire & I \times Cord with transparent casing Kit to hang horizontally or vertically included.

Ceiling plate / Canopy

 $2\,x$ mini canopies H 1.55cm $\,x$ Dia 4cm, in matching finish to Orion.

Also available to order separately:

I \times Side Entry Adapter for mini canopy, which enables LED driver to be surface mounted (increases height of mini canopy to 3.1cm). I \times Deep Canopy that can mount LED driver in canopy if required (H 6.5cm \times Dia I 3cm).

Ix Ceiling plate cover for junction box to mount mini canopy.

Weight

Product (net): 2.41 kg Boxed (gross): 3.32 kg




For more information please contact:

US & Canada Inquiries: +1 212 804 8477 - sales@leebroom.com

LEE BROOM

ORION GLOBE LIGHT (IIO-I30V)





Must be installed with LED driver

LED driver to be installed remotely in suitable sized cavity / housing Refer to LED driver specification sheet for correct size of LED driver supplied with your particular Orion set-up.

PRODUCT DETAILS

N	h	n	_	^

Orion Globe Light

Finish & Product Code

Polished Gold ORI0110
Polished Gunmetal ORI0111

Materials

Opal glass globe, steel tube

Illumination

7.6W, 2700k, 377 lumen, 24VDC, CRI 85 Supplied with separate LED driver with 110-130V input.

Dimming

Dimmable. Lutron C.L dimmers recommended for up to 8 units For more than 8 units, please contact us.

Certification

UL, cULus



Year of Design

2018

Dimensions

H 13cm x W 87.5cm - H 5 1/8 in x W 34 1/2 in

Suspension

Length: 500cm - 196 1/8 in

I \times Adjustable steel tensile wire & I \times Cord with transparent casing Kit to hang horizontally or vertically included.

Ceiling plate / Canopy

 $2 \times mini$ canopies in matching finish to Orion. H 1.55cm \times Dia 4cm - H $\frac{1}{2}$ in \times Dia 1 $\frac{1}{2}$ in

Also available to order separately:

I x Side Entry Adapter, which enables LED driver to be surface mounted (increases height of mini canopy to 3.1cm / 1½ in). I x Deep Canopy that can mount LED driver in canopy if required (H 6.5cm x Dia 13cm - H $2\frac{1}{2}$ in x Dia $5\frac{1}{6}$ in).

Ix Ceiling plate cover for junction box to mount mini canopy.

Weight

Product (net): 2.41 kg / 5.31 lbs Boxed (gross): 3.32 kg / 7.32 lbs



For more information please contact:

US & Canada Inquiries: +1 212 804 8477 - sales@leebroom.com